

DESCRIPTION

Johnstone's Acrylic Gloss is a premium quality, water-borne gloss formulated for interior and exterior use on wood and suitably primed metal surfaces. It provides a low odour, high opacity finish that is quick drying and non-yellowing.

RECOMMENDED USES



Suitable for interior and exterior use.

TYPE OF SUBSTRATE

Wood and metal.

COLOUR RANGE

Over 10,200 colours are available via the Johnstone's Tinting System.

FINISH

Gloss.

VOLUME SOLID

38%

COVERAGE



Approximately 9–11 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME



Touch dry in 1–2 hours.
Recoat after 6 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Protect from frost.

THINNER

Clean water.

VOC CONTENT

Medium VOC content 8–24.99%
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 150g/l (2007) / 130g/l (2010).
This product contains max 100g/l VOC.

FILM THICKNESS

Wet: 100µm, dry: 38µm.

KEY PROPERTIES

- Hard wearing, non-yellowing and washable.
- High opacity pigments provide excellent covering power.
- A quick drying, low odour, water-borne gloss finish for interior and exterior use.

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime bare wood or metal surfaces with the appropriate Johnstone's Primer. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly before applying a pre-coat of Johnstone's Joncyl Water Based Primer Undercoat. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory, on 01924 354100.

APPLICATION



Do not stir. Easy to apply by brush. Do not overspread. Do not apply in temperatures below 10°C or externally when rain is imminent. For best results use a good quality synthetic brush.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- Keep out of the reach of children.

PROFESSIONAL DECORATORS

Safety sheet available for professional user on request.