

5.4

Acrylic Wall Primer Sealer

DESCRIPTION

A quick drying, alkali-resisting primer sealer manufactured from high quality pigments and tough acrylic resin. Ideal for use where its low odour properties, combined with ease of application and speed of drying, allow the work to be completed with a minimum of disruption.

RECOMMENDED USES



Primes and seals plaster, plasterboard, cement render, timber, bare masonry, interior stone and fibre cement boards.

SPECIAL PROPERTIES

Good sealing properties. Quick drying and low odour.

COLOUR RANGE

Brilliant White.

FINISH

Matt.

VOLUME SOLID

30%

COVERAGE



Johnstone's Acrylic Wall Primer Sealer will cover at the rate of approximately 10 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME



Touch dry in 30 minutes.
Recoat after 4 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. PROTECT FROM FROST.

THINNER

Water.

VOC CONTENT

MINIMAL VOC CONTENT 0–0.29%.
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/g): 50g/l (2007) / 30g/l (2010).
This product contains max 3g/l VOC.

FILM THICKNESS

Wet: 100µm, dry: 30µm.

SIZE

5 Litre.

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Hard wall plasters should be scored with coarse glasspaper. Avoid the inhalation of dust. Wear a suitable face mask when dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory on 01924 354100.

APPLICATION



Stir well before use. Apply one full coat, brushing firmly into the surface. Porous surfaces should be sealed with a first coat of Johnstone's Acrylic Wall Primer Sealer thinned with up to 20% clean water. Allow 4 hours to dry under normal conditions, before applying the required paint finish. For best results, apply by brush as this assists the primer to penetrate the surface. Alternatively, Johnstone's Acrylic Wall Primer Sealer can be applied by airless spray. Allow fresh plaster to dry thoroughly before application. Do not apply when air or surface temperature is below 10°C.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- When spraying do not breathe spray, wear suitable respiratory protective equipment.
- Keep out of the reach of children.

PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.



SigmaKalon DECORATIVE COATINGS UK AND IRELAND, SIGMAKALON UK LIMITED

Huddersfield Road, Birstall, Batley, West Yorkshire WF17 9XA Telephone: 01924 354000 Facsimile: 01924 354001 www.johnstones-paints.co.uk