

5.2

Aluminium Wood Primer

DESCRIPTION

A solvent-borne blend of fine grade aluminium and high quality resin. Formulated for interior and exterior use on new or bare timber it provides a barrier against the oily exudations of naturally resinous timber and can be used as a sealer on weathered creosote or smoke damaged surfaces and is also self-knotting.

RECOMMENDED USES



For use on new or bare timber. Seals weathered creosote or smoke damaged surfaces. Primes resinous, scorched and smoke damaged timber and is also self knotting.

SPECIAL PROPERTIES

Can be used as a sealer on weathered creosote or smoke damaged surfaces.

COLOUR RANGE

Metallic Grey.

FINISH

Matt.

VOLUME SOLID

37%

COVERAGE



Johnstone's Aluminium Wood Primer will cover at the rate of approximately 13–15 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME



Touch dry in 4–6 hours.
Recoat after 16–24 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. PROTECT FROM FROST.

THINNER

TC2 Thinner and Cleaner.

VOC CONTENT

HIGH VOC CONTENT 25–50%.
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/g): 450g/l (2007).
This product contains max 400g/l VOC.

FILM THICKNESS

Wet: 75µm, dry: 28µm.

SIZE

1 Litre, 2.5 Litre and 5 Litre.

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Wash down oily timbers such as teak with White Spirit and allow to dry. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical

APPLICATION



Stir well before use. Easy to apply by brush paying particular attention to the end grain.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with TC2 Thinner and Cleaner. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- PAINT UN1263.
- FLAMMABLE.
- Contains White Spirit.
- DANGEROUS FOR THE ENVIRONMENT.
- Toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment.
- Avoid release to the environment.
- Contains Cobalt Carboxylate. May produce an allergic reaction.
- Keep away from sources of ignition – No smoking.
- Repeated exposure may cause skin dryness or cracking.
- Ensure maximum ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner – DO NOT USE SOLVENT OR THINNERS.
- When applying to large interior surfaces or in confined spaces, wear a suitable cartridge respirator or air fed respiratory protective equipment.
- If swallowed, seek medical advice immediately and show the container or label.
- Keep out of the reach of children.

PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.



SigmaKalon DECORATIVE COATINGS UK AND IRELAND, SIGMAKALON UK LIMITED

Huddersfield Road, Birstall, Batley, West Yorkshire WF17 9XA Telephone: 01924 354000 Facsimile: 01924 354001 www.johnstones-paints.co.uk