

DESCRIPTION

Johnstone's Aqua Undercoat is a water based undercoat ideal for interior and exterior wood and metal. Specially formulated to give all the application and appearance characteristics of traditional undercoat with the added advantage of being quick drying and low odour during application. Johnstone's Aqua Undercoat should be used in conjunction with Johnstone's Aqua Gloss to give the best possible finish.

RECOMMENDED USES



Suitable for interior and exterior use.

TYPE OF SUBSTRATE

Ideal for interior and exterior wood and metal.

COLOUR RANGE

Brilliant White, Magnolia, Light Grey & Dark Grey.

FINISH

Undercoat.

VOLUME SOLID

39%

COVERAGE



Approximately 10–12 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME



Touch dry in 1-2 hours.
Recoat after 4-6 hours.

TRANSPORTATION & STORAGE

Avoid the risk of spillage, always store and transport in a secure upright position. Protect from frost.

THINNER

Not applicable.

VOC CONTENT

Low VOC content 0.3–7.99%
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.
EU limit value for this product (Cat A/d): 150g/l (2007) / 130g/l (2010).
This product contains max 10g/l VOC.

FILM THICKNESS

Wet: 100µm, dry: 39µm.

KEY PROPERTIES

- Application characteristics of traditional undercoat.
- Quick drying.
- Low solvent, low odour.
- Can be used on surfaces such as radiators and pipes, complete the whole room in a water based system.

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime bare wood surfaces with Johnstone's Aqua Undercoat. Prime all other bare surfaces with the appropriate Johnstone's primer. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory, on 01924 354100.

APPLICATION



Stir well before use. Easy to apply by brush.
Avoid overspreading. Do not apply in temperatures below 10°C or externally when rain is imminent.
For best results use a good quality synthetic brush.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- Keep out of the reach of children.

SIZES

1 Litre, 2.5 Litre, 5 Litre.

PROFESSIONAL DECORATORS

Safety sheet available for professional user on request.