

## DESCRIPTION

A pliolite resin based paint specially formulated for application to damp interior wall surfaces. Can be left as a finish in its own right or as a damp proofing primer/sealer prior to overpainting with Johnstone's Anti-Mould Acrylic, or other Johnstone's decorative finish. It incorporates a water-reactive agent which takes care of residual surface moisture, but this does not remove the need to repair any structural faults which allow water to penetrate into the fabric of the wall.

## RECOMMENDED USES



Can be used over damp interior wall surfaces, either as a primer/sealer prior to overpainting or as a finish in its own right.

## SPECIAL PROPERTIES

Incorporates a water-reactive agent which eliminates residual surface moisture.

## COLOUR RANGE

White.

## FINISH

Matt.

## VOLUME SOLID

36%

## COVERAGE



Johnstone's Damp Proof Paint will cover at the rate of approximately 4 square metres per litre. It is important to ensure that this total film thickness is achieved – do not overspread.

## DRYING TIME



Touch dry in 2–3 hours.  
Recoat after 16–24 hours.

## TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

## CLEANER

White Spirit.

## VOC CONTENT

HIGH VOC CONTENT 25–50%.

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/I): 600g/l (2007) / 500g/l (2010). This product contains max 500g/l VOC.

## FILM THICKNESS

Wet: 250µm, dry: 90µm.

## SIZE

5 Litre

## PREPARATION

This paint should be applied preferably to unpainted masonry surfaces. However, if these have been previously painted, remove as much of the old paint as possible by thorough scraping and wire brushing. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Treat any mould or lichen with Johnstone's Sterilisation Wash before removing with a scraper or stiff brush, then treat surface again with Johnstone's Sterilisation Wash. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory on 01924 354100.

## APPLICATION



Stir well before use. A thick film is necessary for maximum effectiveness. For the professional contractor this can best be achieved by airless spray in one application. Brush application can be employed, in which case two coats are recommended to achieve the required film thickness, allowing 16–24 hours between coats. Follow with subsequent Johnstone's decorative finish, or leave as a finish in its own right.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- PAINT UN1263.
- FLAMMABLE.
- IRRITATING TO EYES AND SKIN.
- Contains Cement and Solvent Naphtha light aromatic.
- MAY CAUSE SERIOUS DAMAGE TO EYES.
- MAY CAUSE SENSITISATION BY SKIN CONTACT.
- Keep away from sources of ignition – No smoking.
- Harmful to aquatic organisms. May cause long term adverse effects in the aquatic environment.
- Avoid release to the environment.
- Repeated exposure may cause skin dryness or cracking.
- Ensure maximum ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner – DO NOT USE SOLVENT OR THINNERS.
- When applying to large interior surfaces or in confined spaces, wear a suitable cartridge respirator or air fed respiratory protective equipment.
- When spraying do not breathe spray, wear suitable respiratory protective equipment.
- If swallowed, seek medical advice immediately and show the container or label.
- Keep out of the reach of children.

## PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.

