

DESCRIPTION

Exterior Universal Primer is a high quality pre-treatment for use under most conventional paint and varnish systems. Suitable for exterior use, it binds and protects softwood against rot and surface mould including wet rot, dry rot, blue stain and fungi. Use only in accordance with the directions on the label.

AVAILABLE IN

1 litre size.

COLOUR RANGE

Clear.

RECOMMENDED USES



Suitable for exterior use.

TYPES OF SUBSTRATE

Protects exterior softwood against surface mould, wet rot, dry rot, blue stain and fungi.

COVERAGE



Approximately 10–15 square metres per litre depending on the nature and porosity of the timber.

DRYING TIME



Touch dry in 2–3 hours.
Recoat after 16–24 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure, upright position.
STORE AWAY FROM HEAT AND FLAME.

THINNER

White Spirit.

VOC CONTENT

VERY HIGH VOC CONTENT MORE THAN 50%
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

PREPARATION

All surfaces should be clean, dry (moisture content not more than 20%) and free from loose and flaking materials.
DO NOT APPLY OVER EXISTING COATINGS.

APPLICATION



Stir thoroughly prior to and during use. Apply by brush and ensure all end grains and joints are treated with each coat.

CLEANING



Remove as much product as possible from brushes before cleaning. Clean brushes immediately after use with White Spirit or Turpentine Substitute. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- STATUTORY CONDITIONS RELATING TO USE
- FOR USE ONLY AS A WOOD PRESERVATIVE.
- APPLY BY BRUSH OR SPRAY. Apply at a rate of 1 litre of product per 10-15 square metres of timber surface.
- FLAMMABLE.
- WEAR SUITABLE PROTECTIVE CLOTHING AND GLOVES.
- DO NOT BREATHE SPRAY. Otherwise wear respiratory protective equipment and eye protection (See HSE Guidance Booklet HS(G)53 : "The Selection, Use and Maintenance of Respiratory Protective Equipment - A Practical Guide").
- Use only in well ventilated areas.
- If swallowed do not induce vomiting, seek medical advice immediately and show this container or label.
- DO NOT CONTAMINATE ground or watercourses with chemicals or used container.
- COVER WATER STORAGE TANKS before application.
- DO NOT CONTAMINATE FOOD STUFFS, EATING UTENSILS OR FOOD CONTACT SURFACES.
- DANGEROUS TO FISH AND OTHER AQUATIC LIFE.
- REMOVE OR COVER ALL FISH TANKS AND BOWLS before application.
- AVOID ALL CONTACT WITH PLANT LIFE.
- UNPROTECTED PERSONS AND ANIMALS SHOULD BE KEPT AWAY FROM TREATED AREAS FOR 48 HOURS OR UNTIL SURFACES ARE DRY.
- THIS MATERIAL AND ITS CONTAINER must be disposed of in a safe way.
- ALL BATS ARE PROTECTED UNDER THE WILDLIFE AND COUNTRYSIDE ACT 1981. BEFORE TREATING ANY STRUCTURE USED BY BATS, CONSULT THE ENGLISH NATURE, SCOTTISH HERITAGE, THE COUNTRYSIDE COUNCIL FOR WALES OR THE DEPARTMENT OF THE ENVIRONMENT FOR NORTHERN IRELAND.
- READ ALL PRECAUTIONS BEFORE USE (HSE No. 7070).
- Keep away from sources of ignition - No smoking.
- WASH HANDS AND EXPOSED SKIN before meals and after use.
- WASH ALL CONTAMINATION from skin or eyes immediately.
- VENTILATE TREATED AREAS THOROUGHLY after application.
- UNTIL DRY, TREATED AREAS CAN POSE A FIRE RISK.
- KEEP OUT OF THE REACH OF CHILDREN.
- Keep only in original container.
- Keep container tightly closed.
- KEEP IN A SAFE PLACE.
- Safety data sheet available for professional user on request.
- HARMFUL: May cause lung damage if swallowed.
- FLAMMABLE
- Harmful to aquatic organisms. May cause long term adverse effects in the aquatic environment.
- Avoid release to the environment.
- Repeated exposure may cause skin dryness or cracking.
- Contains Dichlofluamid, may produce an allergic reaction.
- CONTAINS: Dichlofluamid 0.5% W/W (4.0g/litre) and Naphtha (petroleum) hydrotreated heavy.
- This product is approved under the Control of Pesticides Regulations 1986 for use as directed.
HSE No. 7070.



PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.