

DESCRIPTION

A high quality product for application over all suitably primed interior surfaces to reduce the spread of fire and increase public safety. Ideal for use in areas where low odour paints are required such as food preparation areas, hospitals, schools and public buildings.

RECOMMENDED USES



Suitable for interior use.

SPECIAL PROPERTIES

High quality product for application over suitably primed surfaces. Low odour. Tested to BS476 Part 6 and 7.

TYPE OF SUBSTRATE

All suitably primed interior surfaces.

COLOUR RANGE

Available in a range of NCS colours available on the tinting system.

FINISH

Eggshell.

VOLUME SOLID

32.9%.

COVERAGE



Flame Retardant Acrylic Eggshell will cover approximately 10–12 square metres per litre depending on the nature and porosity of the surface being painted and the method of application.

DRYING TIME



Touch dry in 1–2 hours.
Recoat after 4–6 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

THINNER

Flame Retardant Acrylic Eggshell can be thinned with up to 10% clean water.

VOC CONTENT

LOW VOC CONTENT 0.30–7.99%
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.
EU limit value for this product (Cat A/i): 140g/l (2007) / 140g/l (2010).
This product contains max 80g/l VOC.

FILM THICKNESS

Wet: 100µm, dry: 33µm.

PREPARATION

Surfaces must be sound, clean, dry and free from all loose and flaking materials, dirt, grease or other surface contaminants. Rub down previously painted surfaces with a fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. New or bare surfaces should be coated with a coat of Johnstone's Flame Retardant Acrylic Eggshell thinned with up to 10% clean water. New wood surfaces should be pre-treated with two coats of Johnstone's Intumescent Basecoat followed by two coats of Flame Retardant Acrylic Eggshell. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead.

APPLICATION



Stir thoroughly before use. Apply by brush, roller or spray as required. For spray applications, thinning may be required.

Airless Spray: 017-019 thou tip,
200 bars (2000-3000 psi)

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with clean water. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Use only in well ventilated areas.
- Avoid contact with skin and eyes.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- When spraying, do not breathe spray, wear suitable respiratory protective equipment.
- Keep out of the reach of children.

SIZE

5 Litre.

PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.

