

6.2 Flame Retardant Vinyl Matt

DESCRIPTION

An excellent quality, easy to apply product. This quick dry formulation and alkali resistant pigments make it ideal for use on internal wall surfaces and ceiling areas where a tough, washable hard wearing finish is required.

RECOMMENDED USES

INTERIOR Suitable for interior use.



SPECIAL PROPERTIES

Quick dry, alkali resisting coating. Low odour. Tested to BS476 Part 6 and 7.

TYPE OF SUBSTRATE

All interior walls and ceiling areas.

COLOUR RANGE

Available in a range of NCS colours available on the tinting system.

FINISH

Matt.

VOLUME SOLID

31.4%.

COVERAGE

COVERAGE Flame Retardant Vinyl Matt will cover approximately 10–12 square metres per litre depending on the nature and porosity of the surface being painted and the method of application.



DRYING TIME

RECDAT Touch dry in 1–2 hours.
Recoat after 4–6 hours.



TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position.

THINNER

Flame Retardant Vinyl Matt can be thinned with up to 10% clean water.

VOC CONTENT

LOW VOC CONTENT 0.30–7.99%
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/i): 140g/l (2007) / 140g/l (2010).
This product contains max 15g/l VOC.

FILM THICKNESS

Wet: 100µm, dry: 31.4µm.

PREPARATION

Surfaces must be sound, clean, dry and free from all loose and flaking materials, dirt, grease or other surface contaminants. Rub down previously painted surfaces with a fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. New or bare surfaces should be coated with a coat of Johnstone's Flame Retardant Matt thinned with up to 10% clean water. New wood surfaces should be pre-treated with two coats of Johnstone's Intumescent Basecoat followed by two coats of Flame Retardant Vinyl Matt. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead.

APPLICATION

APPLICATION METHOD Stir thoroughly before use. Apply by brush, roller or spray as required. For spray applications, thinning may be required.



Airless Spray: 017-019 thou tip,
200 bars (2000-3000 psi)

CLEANING

CLEAN IN WATER Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with clean water. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.



PRECAUTIONS

- Use only in well ventilated areas.
- Avoid contact with skin and eyes.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- When spraying, do not breathe spray, wear suitable respiratory protective equipment.
- Keep out of the reach of children.

SIZE

5 Litre.

PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.



SigmaKalon DECORATIVE COATINGS UK AND IRELAND, SIGMAKALON UK LIMITED

Huddersfield Road, Birstall, Batley, West Yorkshire WF17 9XA Telephone: 01924 354000 Facsimile: 01924 354001 www.johnstones-paints.co.uk