

## DESCRIPTION

A high performance, water-borne, combined primer and undercoat specifically formulated for use on medium density fibreboards. It provides a low odour, quick drying alternative to conventional solvent-borne primers producing an ideal surface for overcoating with subsequent topcoat.

## RECOMMENDED USES



As a primer for MDF, especially routed, to seal prior to application of subsequent topcoat. Also can be used on chipboard, blockboard, planed timber and other wood composites.

## SPECIAL PROPERTIES

High build with excellent adhesion. Quick drying and low odour.

## COLOUR RANGE

Brilliant White.

## FINISH

Matt.

## VOLUME SOLID

36%.

## COVERAGE



Johnstone's MDF Primer will cover at the rate of approximately 12–14 square metres per litre, depending on the nature and porosity of the surface being painted.

## DRYING TIME



Touch dry in 30 minutes.  
Recoat after 1–2 hours.

## TRANSPORTATION &amp; STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. PROTECT FROM FROST.

## THINNER

Water.

## VOC CONTENT

LOW VOC CONTENT 0.30–7.99%  
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 150g/l (2007) / 130g/l (2010).  
This product contains max 15g/l VOC.

## FILM THICKNESS

Wet: 77µm, dry: 27µm.

## SIZE

1 Litre, 2.5 Litre and 5 Litre.

## PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime bare metal surfaces such as nail heads with the appropriate Johnstone's Primer. Rub down previously painted surfaces with fine waterproof abrasive paper. Avoid the inhalation of dust. Wear a suitable face mask when dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory on 01924 354100.

## APPLICATION



Stir well. Easy to apply by brush or roller. Also suitable for application by spray. A second coat serves as an excellent undercoat. Do not apply in temperatures below 10°C.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- PAINT PRODUCT.
- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- When spraying do not breathe spray, wear suitable respiratory protective equipment.
- Keep out of the reach of children.

## PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.

