

5.8

Multi Surface Primer

DESCRIPTION

A quick drying primer with excellent adhesion properties making it ideal for use on problem areas such as glazed tiles and smooth melamine surfaces. Based on a water based acrylic primer for maximum durability. Also suitable for priming more conventional substrates such as wood and metal etc.

RECOMMENDED USES



Primes melamine, powder coat, glazed tiles, matt tiles, quarry tiles, glass and suitably prepared ferrous and non-ferrous metals.

SPECIAL PROPERTIES

Excellent adhesion to non-porous surfaces. Quick drying and low odour.

COLOUR RANGE

Brilliant White.

FINISH

Matt.

VOLUME SOLID

38%

COVERAGE



Johnstone's Multi-Surface Primer will cover at the rate of approximately 13–15 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME



Touch dry in 30 minutes.
Recoat after 4–6 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. PROTECT FROM FROST.

THINNER

Water.

VOC CONTENT

LOW VOC CONTENT 0.30–7.99%.
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/i): 140g/l (2007) / 140g/l (2010).
This product contains max 10g/l VOC.

FILM THICKNESS

Wet: 80µm, dry: 30µm.

SIZE

1 Litre and 2.5 Litre.

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Exposed nail and screw heads should be treated with Johnstone's Water Based Metal Primer. Lightly sand the surface with a fine waterproof abrasive paper and wipe clean. Wear a suitable face mask when dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory on 01924 354100.

APPLICATION



Stir well before use. Suitable for application by brush. Do not apply when air or surface temperature is below 10°C.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- Keep out of the reach of children.

PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.



SigmaKalon DECORATIVE COATINGS UK AND IRELAND, SIGMAKALON UK LIMITED

Huddersfield Road, Birstall, Batley, West Yorkshire WF17 9XA Telephone: 01924 354000 Facsimile: 01924 354001 www.johnstones-paints.co.uk