

## DESCRIPTION

Based on a tough acrylic resin providing a quick drying, low odour finish. Ideal for light traffic areas where low odour and minimum disruption times are important. Three coats can be applied in a day.

## RECOMMENDED USES



Ideal for light traffic areas and absorbent porous surfaces. Excellent on timber floors and where rapid re-occupancy is required.

## SPECIAL PROPERTIES

Low odour, quick drying and easy to apply.

## COLOUR RANGE

Tile Red; Dark Grey (18B25); Morning Mist (10A03).

## FINISH

Mid-sheen.

## VOLUME SOLID

29%

## COVERAGE



Johnstone's Quick Dry Floor Paint will cover at the rate of approximately 10 square metres per litre depending on the nature and porosity of the surface being painted.

## DRYING TIME



Touch dry in 1–2 hours.  
Recoat after 4–6 hours.  
Note: The coating must be fully cured for a minimum of 24 hours in well ventilated conditions before use.

## TRANSPORTATION &amp; STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. PROTECT FROM FROST.

## THINNER

Water.

## VOC CONTENT

MEDIUM VOC CONTENT 8–24.99%  
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/I): 140g/l (2007) / 140g/l (2010).  
This product contains max 100g/l VOC.

## FILM THICKNESS

Wet: 100µm, dry: 30µm.

## SIZES

5 Litre.

## PREPARATION

All surfaces to be painted should be sound, clean, dry and free from dust, laitance and loose or friable material. An effective damp proof membrane must be present beneath masonry floors and new concrete floors should preferably be allowed to mature or thoroughly dry out before painting. Porous surfaces must first be sealed with a thinned coat (by up to 10% by volume with water) of Johnstone's Quick Dry Floor Paint, taking care not to over thin. Prime new or bare metal with Johnstone's Water Based Metal Primer.

Note: Do not apply Johnstone's Quick Dry Floor Paint on power floated/case hardened concrete where silicate hardeners have been used, Terrazzo and Granolithic or substrates that are cold, in damp conditions or where an effective damp proof membrane does not exist. Do not use in areas subject to constant movement of car tyres or in heavy industrial or aggressive environments.

## APPLICATION



Stir well before use. On absorbent porous surfaces, the first coat should be thinned where necessary to ease brushing. Apply by brush or roller. Do not apply when air or surface temperature is below or likely to fall below 10°C. If more than one can of a colour is to be used in the same area, intermix before use.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- PAINT PRODUCT.
- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- Keep out of the reach of children.

## PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.

