

DESCRIPTION

A quick drying, single pack anti-corrosive primer for steel. Suitable for use under a wide variety of conventional finishes, combining excellent adhesion and ease of application.

RECOMMENDED USES



An anti-corrosive primer for ferrous metals and all suitably prepared non-ferrous substrates.

SPECIAL PROPERTIES

Excellent anti-corrosive properties on properly prepared steel.

COLOUR RANGE

Red Oxide; Grey; White.


FINISH

Matt.

VOLUME SOLID

34%

COVERAGE



Johnstone's Quick Dry Zinc Phosphate Primer will cover at the rate of approximately 11 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME



Touch dry in 2–4 hours.
Recoat after 16 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

CLEANER

TC2 Thinner and Cleaner.

VOC CONTENT

HIGH VOC CONTENT 25–50%.
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.
EU limit value for this product (Cat A/i): 600g/l (2007) / 500g/l (2010).
This product contains max 450g/l VOC.

FILM THICKNESS

Wet: 75µm, dry: 35µm.

SIZE

2.5 Litre and 5 Litre (White available in 5 Litre only).

PREPARATION

STEEL: Blast cleaned to SIS-Sa 2½ minimum or mechanically prepared to SIS-St 3 minimum. Previous suitable coats should be clean, dry and abraded if necessary. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory on 01924 354100.

APPLICATION



Stir thoroughly before use. Easy to apply by brush.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with TC2 Thinner and Cleaner. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- PAINT UN1263
- FLAMMABLE.
- DANGEROUS FOR THE ENVIRONMENT.
- Toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment.
- Avoid release to the environment.
- Contains TriZincBisOrthophosphate.
- Contains Ethyl Methyl Ketoxime – May produce an allergic reaction.
- Keep away from sources of ignition – No smoking.
- Repeated exposure may cause skin dryness or cracking.
- Ensure maximum ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner – **DO NOT USE SOLVENT OR THINNERS.**
- When applying to large interior surfaces or in confined spaces, wear a suitable cartridge respirator or air fed respiratory protective equipment.
- If swallowed, seek medical advice immediately and show the container or label.
- Keep out of the reach of children.

PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.

