

## DESCRIPTION

A solvent-borne protective gloss finish formulated for interior and exterior use on most metal and wood surfaces. Based on an alkyd resin and containing red oxide pigments it provides long term protection and helps to prevent rust.

## RECOMMENDED USES



Structural steel and timber surfaces.

## SPECIAL PROPERTIES

Excellent covering power. Long term protection.

## COLOUR RANGE

Red Oxide.

## FINISH

Gloss.

## VOLUME SOLID

41%

## COVERAGE



Johnstone's Red Oxide Paint will cover at the rate of approximately 14–16 square metres per litre depending on the nature and porosity of the surface being painted.

## DRYING TIME



Touch dry in 4–6 hours.  
Recoat after 16–24 hours.

## TRANSPORTATION &amp; STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

## CLEANER

White Spirit.

## VOC CONTENT

HIGH VOC CONTENT 25–50%.

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 400g/l (2007).  
This product contains max 400g/l VOC.

## FILM THICKNESS

Wet: 65µm, dry: 30µm.

## SIZE

2.5 Litre and 5 Litre.

## PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. When painting iron and steel, remove all mill scale and rust. Prime bare surfaces with the appropriate Johnstone's Primer. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Wear a suitable face mask when dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory on 01924 354100.

## APPLICATION



Stir well. Easy to apply by brush or roller.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- PAINT PRODUCT.
- FLAMMABLE.
- Contains Cobalt Carboxylate and Ethyl Methyl Ketoxime. May produce an allergic reaction.
- Keep away from sources of ignition – No smoking.
- Repeated exposure may cause skin dryness or cracking.
- Ensure maximum ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner – **DO NOT USE SOLVENT OR THINNERS.**
- Restrict interior use to small surface areas. Not recommended for interior use on large surface areas or in confined spaces.
- If swallowed, seek medical advice immediately and show the container or label.
- Keep out of the reach of children.

## PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.

