

## DESCRIPTION

Shed & Fence Treatment is formulated to be water repellent and to resist fading. Suitable for above ground rough sawn timber. This special formulation protects exterior timber from the sun's harmful UV rays. Harmless to pets and plants when dry.

## AVAILABLE IN

5 litre size and 9 litre (selected colours)

## COLOUR RANGE

Acorn Gold; Dark Chestnut; Dark Oak; Green; Light Brown; Rustic Red and Ebony.

## RECOMMENDED USES



Suitable for exterior use.

## TYPES OF SUBSTRATE

Rough sawn timber, fences and sheds.

## COVERAGE



Approximately 6 square metres per litre (rough sawn) or 12 square metres per litre (smooth planed) depending on the nature and porosity of the surface being painted.

## DRYING TIME



Allow 2-4 hours between coats.

## TRANSPORTATION &amp; STORAGE

To avoid the risk of spillage, always store and transport in a secure, upright position. PROTECT FROM FROST.

## THINNER

Water.

## VOC CONTENT

MINIMAL VOC CONTENT 0-0.29%  
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/e): 150g/l (2007) / 130g/l (2010).  
This product contains max 3g/l VOC.

## PREPARATION

Ensure all timber is clean, dry and free from surface coatings, such as paint, varnish or polish. If the timber is affected by mould, lichen, algae or moss, use a fungicidal pre-treatment prior to application of Shed & Fence Treatment.

## APPLICATION



Stir Shed & Fence Treatment thoroughly before and during use. Whilst applying ensure gloves are worn to avoid staining hands. Brush liberally and evenly onto exposed surfaces. Wash off any splashes on plants otherwise the foliage may be stained. One coat is required on sound new timber, but two coats will increase the longevity. Old weathered timber or porous timber may require two coats. Do not apply to wet wood, or in temperatures below 10°C or when rain is imminent. Wear a suitable face mask when creating dust. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. PLEASE NOTE: The final colour will depend on the original colour of the wood and number of coats applied.

## CLEANING



Remove as much product as possible from brushes before cleaning. Clean brushes immediately after use with warm soapy water and rinse thoroughly. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- This product contains an algicide, it may be harmful if swallowed.
- Keep out of the reach of children.

## PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.

