

## DESCRIPTION

Johnstone's Stormshield Quick Dry Stabilising Solution is a penetrating solution formulated for application to surfaces of a highly porous or friable nature. It provides a substrate suitable for further decoration with paints such as Johnstone's Stormshield Smooth Masonry, Stormshield Textured Masonry, Stormshield High Build Mid Sheen Masonry and Jontex High Build Masonry Finishes. The quick drying formula allows the masonry paint to be applied with minimum delay.

## RECOMMENDED USES



Suitable for interior and exterior use.

## TYPE OF SUBSTRATE

Concrete, cement rendering, brick, stone, blockwork and pebble dash.

## COLOUR RANGE

Clear (once dry).

## FINISH

Not Applicable.

## VOLUME SOLID

9%

## COVERAGE



Approximately 6–10 square metres per litre depending on the nature and porosity of the surface.

## DRYING TIME



Touch dry in 1–2 hours.  
Recoat after 2–4 hours.

## TRANSPORTATION &amp; STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Protect from frost.

## THINNER

Clean water.

## VOC CONTENT

Minimal low VOC content 0–0.29% VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.  
EU limit value for this product (Cat A/h): 50g/l (2007) / 30g/l (2010).  
This product contains max 3g/l VOC.

## FILM THICKNESS

Wet: not applicable, dry: not applicable.

## KEY PROPERTIES

- Quick drying, low odour and overcoatable in 2–4 hours.
- Binds friable or chalking surfaces to produce a surface suitable for further decoration.
- Highly penetrative water-borne formulation.

## PREPARATION

All surfaces to be treated should be clean, dry and free from loose and flaking material. Repair cracks and defective areas and treat fungal or algal growth with Fungicidal or Sterilisation Wash as directed. Wear a suitable face mask when creating dust.

**Do not** use Quick Dry Stabilising Solution on new/sound surfaces. Apply a thinned coat of Masonry Paint (see can for details).

For further advice contact Technical Advisory, on 01924 354100.

## APPLICATION



Stir well. Easy to apply by brush or roller. Also suitable for application by spray. Not suitable for use on non-absorbent surfaces. Do not apply under conditions of extreme cold (less than 10°C) or externally when rain is imminent. The product will appear pale blue in the container to enable the user to observe which areas have been coated. The product dries clear.

## CLEANING



Remove as much product as possible from the application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- When spraying do not breathe spray, wear suitable respiratory protective equipment.
- Keep out of the reach of children.

## SIZES

5 Litre.

## PROFESSIONAL DECORATORS

Safety sheet available for professional user on request.