

## DESCRIPTION

Johnstone's Stormshield Stabilising Solution is a penetrating solution formulated for application to surfaces of a highly porous or friable nature. It provides a substrate suitable for further decoration with water-borne paints such as Johnstone's Stormshield Smooth, Stormshield Textured and Jontex High Build Textured Masonry Finishes and also Stormshield Pliolite® Based Masonry Finish.

## RECOMMENDED USES



Suitable for exterior use.

## TYPE OF SUBSTRATE

Concrete, cement rendering, brick, stone, blockwork and pebble dash.

## COLOUR RANGE

White and Clear.


## FINISH

Not Applicable.

## VOLUME SOLID

22%

## COVERAGE



Approximately 6–8 square metres per litre, depending on the nature and porosity of the surface.

## DRYING TIME



Touch dry in 1–2 hours.  
Recoat after 16–24 hours.

## TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Store away from heat and flame.

## CLEANER

White spirit.

## VOC CONTENT

Very high VOC content more than 50% VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/h): 750g/l (2007) / 750g/l (2010). This product contains max 750g/l VOC.

## FILM THICKNESS

Wet: not applicable, dry: not applicable.

## SIZES

5 Litre.

## KEY PROPERTIES

- Binds friable or chalking surfaces to produce a surface suitable for further decoration.
- Highly penetrative solvent-borne formulation.
- Designed for use under water-borne masonry finishes.

## PREPARATION

All surfaces to be stabilised should be clean, dry and free from loose and flaking material. Repair cracks and defective areas and treat fungal or algal growth with Johnstone's Sterilisation Wash as directed. Wear a suitable face mask when creating dust. For further advice contact Technical Advisory, on 01924 354100.

## APPLICATION



Stir well. Easy to apply by brush or roller. Suitable for use under Pliolite®. Apply one coat of Stabilising Solution liberally to a small test area. If this dries to a glossy film, thin with a small quantity of White Spirit to two parts of Stabilising Solution and then test again on another small area. If a glossy film still results, try a blend of equal parts of White Spirit and Stabilising Solution. It is important to ensure that a non-glossy, dried sealed surface is produced.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- Paint UN.1263
- Contains Solvent Naphtha light aromatic.
- Harmful to aquatic organisms. May cause long term adverse effects in the aquatic environment.
- Avoid release to the environment.
- FLAMMABLE
- Repeated exposure may cause skin dryness or cracking.
- Keep away from sources of ignition – No smoking.
- Ensure maximum ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner – Do not use solvent or thinners.
- If swallowed, seek medical advice immediately and show the container or label.
- Keep out of the reach of children.



## PROFESSIONAL DECORATORS

Safety sheet available for professional user on request.



The British Board of Agrément is designated by Government to issue European Technical Approvals based on the assessment of products for construction. Johnstone's products carrying this logo have undergone rigorous independent testing and received approval from the BBA.