

DESCRIPTION

Johnstone's Water Seal is a waterproofing sealer formulated for use on porous exterior walls. It provides a water repellent surface whilst allowing the substrate to breathe without changing the appearance of the substrate. This product is designed only for above ground masonry surfaces. Water Seal will not remedy structural defects.

RECOMMENDED USES



Suitable for exterior use.

TYPE OF SUBSTRATE

Concrete, cement rendering, brick, stone, blockwork and pebble dash.

COLOUR RANGE

Clear.

FINISH

Transparent.

VOLUME SOLID

9%

COVERAGE



Approximately 3–5 square metres per litre, depending on the nature and porosity of the surface.

DRYING TIME



Touch dry in 4–6 hours.
Recoat after 8 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Store away from heat and flame.

CLEANER

White spirit.

VOC CONTENT

Very high VOC content more than 50% VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

FILM THICKNESS

Wet: not applicable, dry: not applicable.

KEY PROPERTIES

- For use on exterior porous walls.
- Provides a water repellent surface whilst allowing the substrate to breathe.
- Does not change the appearance of the substrate.

PREPARATION

All surfaces to be coated should be clean, dry and free from loose and flaking material. Ensure all cracks are repaired. Avoid the inhalation of dust - wear a suitable face mask. For further advice contact Technical Advisory, on 01924 354100.

APPLICATION



Easy to apply by brush or roller. Apply a generous coat to provide maximum protection.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Paint UN1263.
- Contains White Spirit.
- DANGEROUS FOR THE ENVIRONMENT.
- Harmful to aquatic organisms. May cause long term adverse effects in the aquatic environment.
- Avoid release to the environment.
- HARMFUL – May cause lung damage if swallowed.
- FLAMMABLE
- Repeated exposure may cause skin dryness or cracking.
- Keep away from sources of ignition – No smoking.
- Ensure maximum ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner – Do not use solvent or thinners.
- If swallowed, do not induce vomiting, seek medical advice immediately and show the container or label.
- Keep out of the reach of children.

SIZES

5 Litre.

PROFESSIONAL DECORATORS

Safety sheet available for professional user on request.