

1.3 Ultra High Opacity Matt

DESCRIPTION

Johnstone's Ultra High Opacity Matt is a high opacity emulsion designed to achieve the appearance of a two coat application in just one coat. It is water based and easy to use and dries to a tough hard wearing matt finish.

RECOMMENDED USES

INTERIOR



Suitable for interior use.

TYPE OF SUBSTRATE

Interior walls and ceilings.

COLOUR RANGE

Over 6,700 colours are available via the Johnstone's Tinting System.

FINISH

Matt.

VOLUME SOLID

35%

COVERAGE

COVERAGE



Approximately 8 square metres per litre depending on the nature and porosity of the surface.

DRYING TIME

RECOAT



Touch dry in 2 hours.
Recoat after 4 hours.

TRANSPORTATION & STORAGE

Avoid the risk of spillage, always store and transport in a secure upright position. Protect from frost.

THINNER

Clean water.

VOC CONTENT

Low VOC content 0.3–7.99%
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/a): 75g/l (2007) / 30g/l (2010).
This product contains max 20g/l VOC.

FILM THICKNESS

Wet: 100µm, dry: 31µm.

KEY PROPERTIES

- High opacity – designed to achieve the appearance of a two-coat application in just one coat.
- Minimum application time.
- Ease of application.

PREPARATION

Ensure the surface to be painted is clean, dry and free from grease. Remove any loose flaking or powdery material. Rub down glossy surfaces with fine waterproof abrasive paper and rinse thoroughly to provide a key. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory, on 01924 354100.

APPLICATION



Stir well before use and apply by brush, roller or paint pad. Also suitable for application by spray. For brush application, fully load the brush and apply liberally and evenly. Avoid overspreading. When using a medium pile roller or paint pad, apply generously and evenly. Do not apply in damp or cold conditions below 10°C.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- Keep out of the reach of children.

SIZES

5 Litre.

PROFESSIONAL DECORATORS

Safety sheet available for professional user on request.