

Ultra Silk

DESCRIPTION

Johnstone's Ultra Silk is a high opacity silk emulsion that is designed to achieve the appearance of a 2 coat application in 1 coat. Superb covering power makes it the ideal product for work where a quick turnaround is required.

RECOMMENDED USES



Suitable for interior use.

TYPE OF SUBSTRATE

Interior walls and ceilings.

COLOUR RANGE

Brilliant White, Magnolia.

FINISH

Silk.

VOLUME SOLID

30%

COVERAGE



Johnstones Ultra Silk will cover approximately 10 square metres per litre depending on the nature and porosity of the surface being painted. Strong or contrasting colours may require additional coats.

DRYING TIME



Touch dry in 2 hours.
Recoat after 4 hours.

TRANSPORTATION & STORAGE

Avoid the risk of spillage, always store and transport in a secure upright position. **Protect from frost.**

THINNER

Clean water.

VOC CONTENT

EU limit value for this product (Cat A/b): 150g/l (2007) / 100g/l (2010). This product contains maximum 40g/l VOC

FILM THICKNESS

Wet: 100µm, dry: 30µm.

KEY PROPERTIES

- High opacity silk emulsion.
- Superb covering power.
- Minimum application time.

PREPARATION

Ensure the surface to be painted is dry, clean and free from grease. Remove any loose flaking or powdery material. Rub down glossy surfaces with fine waterproof abrasive paper and rinse thoroughly to provide a key. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Seal absorbent surfaces with a solution of up to 1 part water to 4 parts paint. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead.

For further advice contact Technical Advisory. For additional information and free Johnstone's Trade datasheets call 01924 354000 or visit www.johnstonestrade.com

APPLICATION



Stir well before use and apply by brush, roller or paint pad. For brush application, fully load the brush and apply liberally and evenly. Avoid overspreading. When using a medium pile roller or paint pad, apply generously and evenly. Do not apply in damp or cold conditions below 10°C.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- **Paint Product**
- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- Keep out of the reach of children.
- Safety data sheet available for professional user on request.

SIZES

5 Litre.

PROFESSIONAL DECORATORS

Safety sheet available for professional user on request.