

Ultra Undercoat

DESCRIPTION

Johnstone's Ultra Undercoat is a premium quality solvent based undercoat developed for interior and exterior use on wood and metal surfaces. Its exceptional opacity, film build and drip resistance make it ideal for new work projects. It provides the perfect base for finishing with Johnstone's solvent based trim finishes.

RECOMMENDED USES



Suitable for interior and exterior use.

TYPE OF SUBSTRATE

Wood and metal.

COLOUR RANGE

Brilliant white.

FINISH

Undercoat.

VOLUME SOLID

57%

COVERAGE



Johnstone's Ultra Undercoat will cover approximately 16-18 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME



Touch dry in 4-6 hours.
Recoat after 16-24 hours.

TRANSPORTATION & STORAGE

Avoid the risk of spillage, always store and transport in a secure upright position. **Store away from heat and flame.**

CLEANER

White spirit.

VOC CONTENT

EU limit value for this product (Cat A/d): 400g/l (2007) / 100g/l (2010). This product contains maximum 400g/l VOC

FILM THICKNESS

Wet: 60µm, dry: 35µm.

SIZES

1 Litre, 2.5 Litre, 5 Litre.

KEY PROPERTIES

- Exceptional opacity.
- Drip resistance.
- Perfect basecoat for Ultra Gloss.

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime bare surfaces with the appropriate Johnstone's Primer. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly to provide a key. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory. For additional information and free Johnstone's Trade datasheets call 01924 354000 or visit www.johnstonestrade.com

APPLICATION



Stir Well. Easy to apply by brush or roller. Do not apply over polystyrene surfaces.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- **Paint Product**
- Flammable
- Contains Ethyl Methyl Ketoxime. May produce an allergic reaction.
- Repeated exposure may cause skin dryness or cracking.
- Keep away from sources of ignition - No smoking.
- Ensure maximum ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner
- DO NOT USE SOLVENT OR THINNERS.
- Restrict interior use to small surface areas such as doors, window frames and skirting boards. Not recommended for interior use on large surface areas - walls, floors or ceilings - or in confined spaces.
- If swallowed, seek medical advice immediately and show this container or label.
- Keep out of the reach of children.
- Safety data sheet available for professional user on request.

PROFESSIONAL DECORATORS

Safety sheet available for professional user on request.