

## DESCRIPTION

Johnstone's Soft Sheen is a premium quality vinyl mid sheen emulsion formulated for interior use on walls and ceilings. It provides an attractive modern alternative to traditional Vinyl Silk and Vinyl Matt that will withstand normal levels of humidity and can be wiped clean.

## RECOMMENDED USES



Suitable for interior use.

## TYPE OF SUBSTRATE

Plaster and embossed wallcoverings. Also suitable for use on wallboards, concrete, cement rendering, brickwork and blockwork etc.

## COLOUR RANGE

Over 15,500 colours are available via the Johnstone's Tinting System.

## FINISH

Mid sheen.

## VOLUME SOLID

28%

## COVERAGE



Approximately 12–13 square metres per litre depending on the nature and porosity of the surface.

## DRYING TIME



Touch dry in 1–2 hours.  
Recoat after 3–4 hours.

## TRANSPORTATION &amp; STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Protect from frost.

## THINNER

Clean water.

## VOC CONTENT

Low VOC content 0.3–7.99%  
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.  
EU limit value for this product (Cat A/a): 75g/l (2007) / 30g/l (2010).  
This product contains max 10g/l VOC.

## FILM THICKNESS

Wet: 90µm, dry: 25µm.

## KEY PROPERTIES

- A subtle vinyl mid sheen finish alternative to Vinyl Matt and Vinyl Silk.
- Suitable for use on interior walls and ceilings.
- Easy to apply, washable and dirt resistant.

## PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime bare surfaces with the appropriate Johnstone's Primer. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory, on 01924 354100.

## APPLICATION



Stir well. Easy to apply by brush or roller. Also suitable for application by spray. Seal absorbent surfaces with a coat of Soft Sheen thinned up to 10% with clean water. If more than one can of a colour is to be used in the same area, intermix before use. Do not apply in temperatures below 10°C.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- When spraying do not breathe spray, wear suitable respiratory protective equipment.
- Keep out of reach of children.

## SIZES

2.5 Litre, 5 Litre, 10 Litre.

## PROFESSIONAL DECORATORS

Safety sheet available for professional user on request.