

DESCRIPTION

A water-borne metal primer manufactured from high quality pigments and a special acrylic resin. Its excellent anti-corrosive and adhesion properties make it ideal for use on suitably prepared ferrous metals.

RECOMMENDED USES



Primes suitably prepared ferrous metals, such as, steel, iron and galvanised steel.

SPECIAL PROPERTIES

Excellent anti-corrosive properties and adhesion to metal. Quick drying and low odour.

COLOUR RANGE

Grey.

FINISH

Matt.

VOLUME SOLID

32%.

COVERAGE



Johnstone's Water Based Metal Primer will cover at the rate of approximately 10 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME



Touch dry in 2 hours.
Recoat after 4 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. PROTECT FROM FROST.

CLEANER

Water.

VOC CONTENT

LOW VOC CONTENT 0.30–7.99%
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/I): 140g/l (2007) / 140g/l (2010).
This product contains max 80g/l VOC.

FILM THICKNESS

Wet: 100µm, dry: 34µm.

SIZE

2.5 Litre.

PREPARATION

All surfaces to be painted should be sound, clean, dry and free from grease, polish and loose or flaking material. Existing rust or millscale should be removed from iron and steel. Avoid the inhalation of dust. Wear a suitable face mask when dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead.

For further advice contact Technical Advisory on 01924 354100.

APPLICATION



Stir well before use. Easy to apply by brush, roller or spray. Do not thin. Do not apply when air or surface temperature is below or likely to fall below 10°C.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- PAINT PRODUCT.
- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- When spraying do not breathe spray, wear suitable respiratory protective equipment.
- Keep out of the reach of children.

PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.

